



ADDENDUM

Public Building Commission of Chicago | Richard J. Daley Center | 50 West Washington Street, Room 200 | Chicago, Illinois 60602 | (312) 744-3090 | pbcchicago.com

ADDENDUM NO.: 01
PROJECT NAME: Kenwood Academy High School Link and Mechanical Project
PROJECT NO.: 05326
CONTRACT NO.: C1602
DATE OF ISSUE: October 6, 2022

NOTICE OF CHANGES, MODIFICATIONS, OR CLARIFICATIONS TO CONTRACT DOCUMENTS

The following changes, modifications, or clarifications are hereby incorporated and made an integral part of the Contract Documents. Unless clearly expressed otherwise by this Addendum, all terms and conditions defined in the original Contract Documents shall continue in full force and effect and shall have the same meaning in this Addendum. Issued Addenda represent responses/clarifications to various inquiries. Contractors shall be responsible for including all associated labor/material costs in its bid. Drawings/specifications corresponding to inquiry responses will be issued with the Issue for Construction Documents, upon issuance of building permit.

ITEM NO. 1: CHANGE TO KEY DATES

Change 1 The **Pre-Bid/Technical Review Meeting Date and Time** has been **RESCHEDULED** to Thursday, October 13, 2022 at 10:00a.m.

ITEM NO. 2: REVISIONS TO BOOK 1 – PBC INSTRUCTIONS TO BIDDERS

None.

ITEM NO. 3: REVISIONS TO BOOK 2 – PBC STANDARD TERMS AND CONDITIONS

None.

ITEM NO. 4: REVISIONS TO BOOK 3 – TECHNICAL SPECIFICATIONS

Change 1 **Book 3 – Kenwood Link – REVISED** Specification Section 00 01 02 Table of Contents.

Change 2 **Book 3 – Kenwood Link – ADDED** Specification Section 08 16 13 Fiberglass Doors.

Change 3 **Book 3 – Kenwood Link – ADDED** Specification Section 08 43 13 – Aluminum-Framed Storefronts.

ITEM NO. 5: REVISIONS TO DRAWINGS

None.

ITEM NO. 6: REQUESTS FOR INFORMATION

RFI-1.

Question: Door schedule sheet A600 Door type #B is detailed as stile/rail aluminum door. There is no specification for aluminum doors other than FRP.

Response: Specification Section 08 43 13 ALUMINUM- FRAMED STOREFRONTS and Specification Section 08 16 13 FIBERGLASS DOORS have been added and are included in this Addendum No. 1.

RFI-2.

Question: There is a spec for Manual Window Shades, but they are never shown in the drawings. Please provide more information regarding the Window Shades.

Response: Manual Window Shades are not required. Specification Section 12 24 00 has been deleted.

This Addendum includes the following attached Specifications and/or Documents:

1. Specification Section 00 01 02 - Table of Contents - for BOOK 3 – KENWOOD LINK
2. Specification Section 08 43 13 – Aluminum Framed Storefronts
3. Specification Section 08 16 13 – Fiberglass Doors

This Addendum includes the following attached Drawings:

None.

END OF ADDENDUM NO. 01

SECTION 00 01 02

TABLE OF CONTENTS

DIVISION 00 - PROCUREMENT AND CONTRACTING REQUIREMENTS

00 00 00	PROJECT MANUAL COVER PAGE	01_11/11/20
00 01 02	TABLE OF CONTENTS	CPS-PBC 24_01/03/22
00 01 11	SUPPLEMENTAL PROJECT INFORMATION	01_11/27/18

DIVISION 01 - GENERAL REQUIREMENTS

01 10 00	SUMMARY OF WORK - LINK	01_11/27/18
01 10 00.01	SUMMARY OF WORK - MEP	01_11/27/18
01 14 11	CONSTRUCTION OPERATIONS AND SITE UTILIZATION PLAN	01_11/27/18
01 23 00	ALTERNATES	01_11/27/18
01 25 00	SUBSTITUTION PROCEDURES	01_11/27/18
01 25 00.01	SUBSTITUTION REQUEST FORM	01_11/27/18
01 32 16	CONSTRUCTION PROGRESS SCHEDULE	01_11/27/18
01 40 00	QUALITY REQUIREMENTS	01_11/27/18
01 42 16	DEFINITIONS	01_11/27/18
01 50 03	TEMPORARY FACILITIES AND CONTROLS – RENOVATION	01_11/27/18
01 50 05	TEMPORARY FACILITIES AND CONTROLS – NEW CONSTRUCTION... ..	01_11/27/18
01 50 10	COMMISSION REPRESENTATIVE FIELD OFFICE	PBC 07_10/10/19
01 56 11	GENERAL DUST, FUME AND ODOR CONTROLS	01_11/27/18
01 57 21	INTEGRATED PEST MANAGEMENT	01_11/27/18
01 60 00	PRODUCT REQUIREMENTS	01_11/27/18
01 62 10	PRE-CONSTRUCTION PROJECT MOCK-UP	01_11/27/18
01 70 00	EXECUTION REQUIREMENTS	01_11/27/18
01 73 29	CUTTING AND PATCHING	01_11/27/18
01 78 23.1	OPERATIONS & MAINTENANCE DATA – COMMISSIONING.....	01_04/26/19
01 79 00	DEMONSTRATION AND TRAINING	01_11/27/18
01 79 00.1	DEMONSTRATION AND TRAINING – COMMISSIONING.....	01_04/26/19
01 91 00	GENERAL COMMISSIONING (Cx) REQUIREMENTS	01_04/26/19
01 91 14	BUILDING ENCLOSURE COMMISSIONING REQUIREMENTS.....	PENDING

DIVISION 02 - EXISTING CONDITIONS

02 13 15	SMALL SCALE DISTURBANCE ASBESTOS CONTAINING MATERIALS	01_11/27/18
02 24 00	ENVIRONMENTAL ASSESSMENT.....	01_11/27/18
02 24 01	ENVIRONMENTAL SCOPE SHEETS.....	01_11/27/18
02 26 00	HAZARDOUS MATERIALS ASSESSMENT	01_11/27/18
02 41 13	SELECTIVE SITE DEMOLITION	01_11/27/18
02 41 16	BUILDING DEMOLITION	01_11/27/18
02 41 19	SELECTIVE DEMOLITION	01_11/27/18
02 82 13	ASBESTOS ABATEMENT – PRIOR TO DEMOLITION	01_11/27/18
02 82 14	ASBESTOS ABATEMENT – INTERIORS.....	01_11/27/18
02 82 15	ASBESTOS ABATEMENT – EXTERIORS.....	01_11/27/18
02 83 19	LEAD-BASED PAINT ABATEMENT	01_11/27/18
02 83 20	SMALL SCALE DIST OF PAINT SURF ASSUMED CONTAIN LEAD	01_11/27/18
02 86 13	HAZARDOUS AND UNIVERSAL WASTE MANAGEMENT	01_11/27/18
02 87 13	ANIMAL EXCREMENT AND CARCASS ABATEMENT	01_11/27/18

DIVISION 03 - CONCRETE

03 30 00	CAST-IN-PLACE CONCRETE	01_11/27/18
03 30 53	MISCELLANEOUS CAST-IN-PLACE CONCRETE	01_11/27/18
03 54 00	CAST UNDERLAYMENT	01_11/27/18

DIVISION 04 - MASONRY

04 20 00	UNIT MASONRY	01_11/27/18
04 20 02	SINGLE-WYTHE UNIT MASONRY.....	01_11/27/18

DIVISION 05 - METALS

05 12 00	STRUCTURAL STEEL FRAMING	01_11/27/18
05 21 00	STEEL JOIST FRAMING	01_11/27/18
05 31 00	STEEL DECKING	01_11/27/18
05 40 00	COLD-FORMED METAL FRAMING.....	01_11/27/18
05 50 00	METAL FABRICATIONS	01_11/27/18
05 52 13	PIPE AND TUBE RAILINGS	01_11/27/18
05 53 05	GRATINGS AND FLOOR PLATES	01_11/27/18
05 75 00	DECORATIVE FORMED METAL	01_11/27/18

DIVISION 06 - WOOD, PLASTICS, AND COMPOSITES

06 10 00	ROUGH CARPENTRY	02_12/14/18
06 20 00	FINISH CARPENTRY	01_11/27/18

DIVISION 07 - THERMAL AND MOISTURE PROTECTION

07 01 50.65	ROOF PATCHING	01_11/27/18
07 11 13	BITUMINOUS DAMPPROOFING	01_11/27/18
07 13 00	SHEET WATERPROOFING	01_11/27/18
07 21 00	THERMAL INSULATION	01_11/27/18
07 21 29	SPRAYED INSULATION	01_11/27/18
07 25 00	WEATHER BARRIERS	01_11/27/18
07 42 13	METAL WALL PANELS	01_11/27/18
07 52 16.11	COLD APPLIED MODIFIED BITUMINOUS MEMBRANE ROOFING	04_12/30/21
07 52 16.12	HOT APPLIED MODIFIED BITUMINOUS MEMBRANE ROOFING	04_12/30/21
07 54 33	FLEXIBLE MEMBRANE ROOFING	01_11/27/18
07 56 00	FLUID APPLIED ROOFING	01_01/28/21
07 62 00	SHEET METAL FLASHING AND TRIM	01_11/27/18
07 71 00	ROOF SPECIALTIES	02_11/30/18
07 72 00	ROOF ACCESSORIES	02_12/30/21
07 81 00	APPLIED FIREPROOFING	01_11/27/18
07 81 23	INTUMESCENT MASTIC FIREPROOFING	01_11/27/18
07 84 00	FIRESTOPPING	01_11/27/18
07 92 00	JOINT SEALANTS	01_11/27/18
07 95 13	EXPANSION JOINT COVER ASSEMBLIES	01_11/27/18

DIVISION 08 - OPENINGS

08 11 13	HOLLOW METAL DOORS AND FRAMES	02_12/30/21
08 16 13	FIBERGLASS DOORS	01_11/27/18

08 31 00	ACCESS DOORS AND PANELS	01_11/27/18
08 43 13	ALUMINUM-FRAMED STOREFRONTS	04_12/30/22
08 51 13	ALUMINUM WINDOWS	02_03/26/19
08 71 00	DOOR HARDWARE	02_05/26/21
08 71 00.01	DOOR HARDWARE SCHEDULE	03_12/30/21
08 80 00	GLAZING	03_08/06/21
08 91 00	LOUVERS	02_10/01/21

DIVISION 09 - FINISHES

09 01 22	GYPSUM PLASTER PATCHING	01_11/27/18
09 05 61	COMMON WORK RESULTS FOR FLOORING PREPARATION	01_11/27/18
09 21 16	GYPSUM BOARD ASSEMBLIES	01_11/27/18
09 22 16	NON-STRUCTURAL METAL FRAMING	01_11/27/18
09 51 00	ACOUSTICAL CEILINGS	02_12/30/21
09 65 00	RESILIENT FLOORING	04_10/01/21
09 91 23	INTERIOR PAINTING	02_12/30/21

DIVISION 10 - SPECIALTIES

10 14 00	SIGNAGE	01_11/27/18
10 26 01	WALL AND CORNER PROTECTION	02_03/15/21
10 44 00	FIRE PROTECTION SPECIALTIES	01_11/27/18

DIVISION 12 - FURNISHINGS

12 24 00	MANUAL WINDOW SHADES	03_06/18/24
12 48 13	ENTRANCE FLOOR MATS AND FRAMES	01_11/27/18

DIVISION 22 - PLUMBING

22 07 19	PLUMBING PIPING INSULATION	01_11/27/18
22 11 16	DOMESTIC WATER PIPING	01_11/27/18
22 11 19	DOMESTIC WATER PIPING SPECIALTIES	02_12/30/21
22 13 16	SANITARY WASTE, VENT AND STORM DRAINAGE PIPING	01_11/27/18
22 14 23	DRAINAGE, PIPING AND SPECIALTIES	02_12/30/21
22 35 00	DOMESTIC WATER PUMPS	02_10/01/21
22 36 00	COMMERCIAL FUEL-FIRED WATER HEATERS	01_11/27/18
22 37 00	SANITARY SEWAGE AND SUMP PUMPS	01_11/27/18
22 40 00	PLUMBING FIXTURES	02_12/30/21
22 66 53	CHEMICAL WASTE PIPING	01_11/27/18

DIVISION 23 - HEATING, VENTILATING AND AIR-CONDITIONING (HVAC)

23 05 03	GENERAL PROVISIONS FOR HVAC WORK	
23 05 05	BASIC HVAC MATERIALS AND METHODS	
23 05 13	COMMON MOTOR REQUIREMENTS FOR HVAC EQUIPMENT	01_11/27/18
23 05 19	METERS AND GAGES FOR HVAC PIPING	01_11/27/18
23 05 23	GENERAL-DUTY VALVES FOR HVAC PIPING	01_11/27/18
23 05 53	IDENTIFICATION FOR HVAC PIPING AND EQUIPMENT	02_04/13/21
23 05 93	TESTING, ADJUSTING, AND BALANCING FOR HVAC	02_12/30/21
23 07 13	DUCT INSULATION	01_11/27/18
23 07 16	HVAC EQUIPMENT INSULATION	01_11/27/18
23 07 19	HVAC PIPING INSULATION	01_11/27/18
23 09 21	Building Automation System-Basic Materials, Interface Devices	07_01/28/21

	and Sensors	
23 09 23	DIRECT-DIGITAL CONTROL SYSTEM FOR HVAC	07_12/30/21
23 09 26	Building Automation System-Sequence of Operation	03_04/03/07
23 09 27	Building Automation System-Commissioning	05_03/25/19
23 21 13	HYDRONIC PIPING	01_11/27/18
23 21 14	HYDRONIC SPECIALTIES	01_11/27/18
23 21 23	HYDRONIC PUMPS	01_11/27/18
23 22 13	STEAM AND CONDENSATE HEATING PIPING	01_11/27/18
23 22 14	STEAM AND CONDENSATE HEATING SPECIALTIES	01_11/27/18
23 23 00	REFRIGERANT PIPING	01_11/27/18
23 25 00	HVAC WATER TREATMENT	01_11/27/18
23 31 00	HVAC DUCTS AND CASINGS	01_11/27/18
23 33 00	AIR DUCT ACCESSORIES	01_11/27/18
23 34 23	HVAC POWER VENTILATORS	02_12/30/21
23 36 00	AIR TERMINAL UNITS	01_11/27/18
23 37 00	AIR OUTLETS AND INLETS	01_11/27/18
23 62 00	PACKAGED COMPRESSOR CONDENSOR UNITS	
23 73 13	MODULAR INDOOR CENTRAL AIR HANDLER	01_11/27/18
23 82 00	CONVECTION HEATING AND COOLING UNITS	03_12/30/21

DIVISION 26 - ELECTRICAL

26 05 05	SELECTIVE DEMOLITION FOR ELECTRICAL	01_11/27/18
26 05 19	LOW-VOLTAGE ELECTRICAL POWER CONDUCTORS AND CABLES	01_11/27/18
26 05 26	GROUNDING AND BONDING FOR ELECTRICAL SYSTEMS	01_11/27/18
26 05 29	HANGERS AND SUPPORTS FOR ELECTRICAL SYSTEMS	01_11/27/18
26 05 33.13	CONDUIT FOR ELECTRICAL SYSTEMS	01_11/27/18
26 05 33.16	BOXES FOR ELECTRICAL SYSTEMS.....	01_11/27/18
26 05 33.23	SURFACE RACEWAYS FOR ELECTRICAL SYSTEMS.....	01_11/27/18
26 05 53	IDENTIFICATION FOR ELECTRICAL SYSTEMS	02_04/13/21
26 05 83	WIRING CONNECTIONS	01_11/27/18
26 08 13	TESTING OF ELECTRICAL SYSTEMS	01_11/27/18
26 09 23	LIGHTING CONTROL DEVICES	02_02/09/21
26 09 36	MODULAR DIMMING CONTROLS	02_02/09/21
26 09 43	LIGHTING CONTROLS.....	02_02/09/21
26 24 16	PANELBOARDS	01_11/27/18
26 27 26	WIRING DEVICES	03_03/19/21
26 28 13	FUSES	01_11/27/18
26 28 16.13	ENCLOSED CIRCUIT BREAKERS	01_11/27/18
26 28 16.16	ENCLOSED SWITCHES	01_11/27/18
26 29 13	ENCLOSED CONTROLLERS.....	01_11/27/18
26 29 23	VARIABLE FREQUENCY MOTOR CONTROLLERS	01_11/27/18
26 51 00	INTERIOR LIGHTING.....	02_02/09/21
26 56 00	EXTERIOR LIGHTING.....	02_02/09/21

DIVISION 27 - COMMUNICATIONS

27 05 03	COMMUNICATIONS GENERAL REQUIREMENTS	01_11/27/18
27 05 53.01	IDENTIFICATION FOR COMMUNICATION SYSTEMS LABELING GUIDELINES	
27 08 00	COMMISSIONING OF COMMUNICATIONS	01_11/27/18
27 15 00	DATA COMMUNICATIONS HORIZONTAL CABLING	02_12/11/20
27 53 15	INTERCOM/MASTER CLOCK & PROGRAM EQUIPMENT INTERFACE ..	01_11/27/18

DIVISION 28 - ELECTRONIC SAFETY AND SECURITY

28 23 07 DVS SYSTEM - EXISTING SCHOOL 01_11/27/18

DIVISION 31 - EARTHWORK

31 13 00 TREE AND LANDSCAPE PROTECTION..... 01_11/27/18

31 23 17 EXCAVATING, BACKFILLING, AND COMPACTING FOR UTILITIES..... 01_11/27/18

DIVISION 32 - EXTERIOR IMPROVEMENTS

32 11 23 AGGREGATE BASE COURSES & CRUSHED STONE DRAINAGE MATERIAL

32 12 16 ASPHALT PAVING 02_10/01/21

32 14 13 PRECAST CONCRETE UNIT PAVING 01_11/27/18

32 14 43 PERMEABLE UNIT PAVING 01_11/27/18

32 16 13 CONCRETE WALKS AND CURBS

32 17 23.13 PAINTED PAVEMENT MARKINGS..... 02_10/01/21

32 18 15 SYNTHETIC GRASS SURFACING SYSTEM - SPORTS FIELDS 02_12/30/21

32 31 19 DECORATIVE METAL FENCES AND GATES 01_11/27/18

32 33 13 SITE BICYCLE RACKS 01_11/27/18

32 92 23 SODDING 01_11/27/18

32 93 00 PLANTS..... 01_11/27/18

DIVISION 33 - UTILITIES

33 41 00 SEWERAGE AND DRAINAGE 01_11/27/18

END OF SECTION

SECTION 08 43 13
ALUMINUM-FRAMED STOREFRONTS

PART 1 - GENERAL

1.01 SECTION INCLUDES

- A. Aluminum framed entrance doors with vision glass.
- B. Weatherstripping.

1.02 REFERENCE STANDARDS

- A. AAMA CW-10 - Care and Handling of Architectural Aluminum from Shop to Site; 2015.
- B. AAMA 609 & 610 - Cleaning and Maintenance Guide for Architecturally Finished Aluminum (Combined Document); 2015.
- C. AAMA 611 - Voluntary Specification for Anodized Architectural Aluminum; 2014 (2015 Errata).
- D. AAMA 1503 - Voluntary Test Method for Thermal Transmittance and Condensation Resistance of Windows, Doors and Glazed Wall Sections; 2009.
- E. AAMA 2605 - Voluntary Specification, Performance Requirements and Test Procedures for Superior Performing Organic Coatings on Aluminum Extrusions and Panels (with Coil Coating Appendix); 2017a.
- F. ASTM B221 - Standard Specification for Aluminum and Aluminum-Alloy Extruded Bars, Rods, Wire, Profiles, and Tubes; 2014.
- G. ASTM B221M - Standard Specification for Aluminum and Aluminum-Alloy Extruded Bars, Rods, Wire, Profiles, and Tubes (Metric); 2013.
- H. ASTM E283 - Standard Test Method for Determining the Rate of Air Leakage Through Exterior Windows, Curtain Walls, and Doors Under Specified Pressure Differences Across the Specimen; 2004 (Reapproved 2012).
- I. ASTM E330/E330M - Standard Test Method for Structural Performance of Exterior Windows, Doors, Skylights and Curtain Walls by Uniform Static Air Pressure Difference; 2014.
- J. ASTM E331 - Standard Test Method for Water Penetration of Exterior Windows, Skylights, Doors, and Curtain Walls by Uniform Static Air Pressure Difference; 2000 (Reapproved 2016).

1.03 ADMINISTRATIVE REQUIREMENTS

- A. Coordinate with installation of other components that comprise the exterior enclosure.
- B. Pre-installation Meeting: Conduct a pre-installation meeting one week before starting work of this section.
 - 1. Ensure required submittals have been provided with sufficient time for review prior to scheduling the Pre-installation Meeting.
 - 2. Review the detailed requirements for the work of this section and to review the drawings and specifications for this work
 - 3. Require attendance by all affected installers including but not limited to

- a. Contractor's Superintendent
 - b. Installer
 - c. Manufacturer/Fabricator Representative
 - d. Other affected Subcontractors
 - e. Architect/Engineer of Record
 - f. Board's Representative
4. Record minutes and distribute copies within 5 days after meeting to participants as well as Architect/Engineer of Record, Board and those affected by decisions made.

1.04 SUBMITTALS

- A. See Section 01 30 00 - Administrative Requirements, for submittal procedures.
- B. Product Data: Provide component dimensions, describe components within assembly, anchorage and fasteners, glass and infill, internal drainage details.
- C. Shop Drawings: Indicate system dimensions, framed opening requirements and tolerances, affected related work, expansion and contraction joint location and details, and field welding required.
 1. Include State of Illinois licensed Structural Engineer's stamp or seal on shop drawings for attachments and anchors.
- D. Samples: Submit two samples on a minimum of 4 inches long illustrating extremes of color in finished aluminum surface.
 1. The right is reserved to require samples of typical fabricated sections, showing joints, exposed fastenings (if any), quality of workmanship, hardware and accessory items, before fabrication of the Work proceeds.
- E. Manufacturer's Certificate: Certify that the products supplied meet or exceed the specified requirements.
- F. Design Data: Provide framing member structural and physical characteristics, engineering calculations signed and sealed by an Illinois licensed Structural Engineer, and dimensional limitations.

1.05 QUALITY ASSURANCE

- A. Designer Qualifications: Design structural support framing components under direct supervision of a Structural Engineer experienced in design of this Work and licensed in Illinois.
- B. Installer Qualifications: Company specializing in performing work of type specified and with at least three years of documented experience.

1.06 DELIVERY, STORAGE, AND HANDLING

- A. Handle products of this section in accordance with AAMA CW-10.
- B. Protect finished aluminum surfaces with wrapping. Do not use adhesive papers or sprayed coatings that bond to aluminum when exposed to sunlight or weather.

1.07 FIELD CONDITIONS

- A. Do not install sealants when ambient temperature is less than 40 degrees F. Maintain this minimum temperature during and 48 hours after installation.

PART 2 - PRODUCTS

2.01 MANUFACTURERS

- A. Aluminum-Framed Storefront and Doors:
 - 1. C.R. Laurence Company, Inc; U.S. Aluminum: www.crl-arch.com/#sle.
 - 2. EFCO Corporation: www.efcocorp.com/#sle.
 - 3. Kawneer North America: www.kawneer.com/#sle.
 - 4. Oldcastle BuildingEnvelope: www.oldcastlebe.com/#sle.
 - 5. Pittco Architectural Metals Inc: www.pittcometals.com/#sle.
 - 6. Tubelite, Inc: www.tubeliteinc.com/#sle.
 - 7. Wausau Window and Wall Systems: www.wausauwindow.com.

2.02 STOREFRONT COMPONENTS

- A. Aluminum Framing Members: Tubular aluminum sections, thermally broken with interior section insulated from exterior, drainage holes and internal weep drainage system.
 - 1. Glazing Stops: Applied.
- B. Glazing: As specified in Section 08 80 00.
- C. Swing Doors: Glazed aluminum.
 - 1. Thickness: 1-3/4 inches.
 - 2. Top Rail: 4 inches wide.
 - 3. Vertical Stiles: 4-1/2 inches wide.
 - 4. Bottom Rail: 10 inches wide.
 - 5. Glazing Stops: Square.
 - 6. Finish: Same as storefront.

2.03 MATERIALS

- A. Extruded Aluminum: ASTM B221 (ASTM B221M).
- B. Fasteners: Stainless steel.
- C. Exposed Flashings: Aluminum sheet, 20 gage, 0.032 inch minimum thickness; finish to match framing members.
- D. Concealed Flashings: Stainless steel, 26 gage, 0.0187 inch minimum thickness.
- E. Sill Flashing Sealant: Elastomeric, silicone or polyurethane, compatible with flashing material.
- F. Sealant for Setting Thresholds: Non-curing butyl type.
- G. Glazing Gaskets: Type to suit application to achieve weather, moisture, and air infiltration requirements.
- H. Glazing Accessories: As specified in Section 08 80 00.

2.04 FINISHES

- A. Superior Performing Organic Coatings: AAMA 2605 multiple coat, thermally cured polyvinylidene fluoride (PVDF) system.

1. Polyvinylidene fluoride (PVDF) multi-coat thermoplastic fluoropolymer coating system, including minimum 70 percent PVDF color topcoat and minimum total dry film thickness of 0.9 mil; color and gloss as indicated on drawings.

B. Color: Clear coat silver or as selected by Architect of Record from manufacturer's standard range.

2.05 HARDWARE

A. Other Door Hardware: As specified in Section 08 71 00.

B. Weatherstripping: Provide weatherstripping as required to meet performance requirements.

C. Sill Sweep Strips: ADA-accessible, resilient seal type, retracting, of neoprene; provide on all doors.

PART 3 - EXECUTION

3.01 EXAMINATION

A. Verify dimensions, tolerances, and method of attachment with other work.

B. Verify that wall openings and adjoining air and vapor seal materials are ready to receive work of this section.

C. Proceed only after unsatisfactory conditions have been corrected. Commencement of work in this section will be an indication of the acceptance of substrate conditions and the Contractor will be held responsible for the satisfactory execution and results of the finished work

3.02 INSTALLATION

A. Attach to structure to permit sufficient adjustment to accommodate construction tolerances and other irregularities.

B. Provide alignment attachments and shims to permanently fasten system to building structure.

C. Align assembly plumb and level, free of warp or twist. Maintain assembly dimensional tolerances, aligning with adjacent work.

D. Provide thermal isolation where components penetrate or disrupt building insulation.

E. Install sill flashings. Turn up ends and edges; seal to adjacent work to form water tight dam.

F. Where fasteners penetrate sill flashings, make watertight by seating and sealing fastener heads to sill flashing.

G. Pack fibrous insulation in shim spaces at perimeter of assembly to maintain continuity of thermal barrier.

H. Set thresholds in bed of sealant and secure them.

I. Install glass in accordance with Section 08 80 00, using glazing method required to achieve performance criteria.

- J. Touch-up minor damage to factory applied finish; replace components that cannot be satisfactorily repaired.

3.03 TOLERANCES

- A. Maximum Variation from Plumb: 0.06 inch per 3 feet non-cumulative or 0.06 inch per 10 feet, whichever is less.
- B. Maximum Misalignment of Two Adjoining Members Abutting in Plane: 1/32 inch.

3.04 ADJUSTING

- A. Adjust operating hardware and sash for smooth operation.

3.05 CLEANING

- A. Remove protective material from pre-finished aluminum surfaces.
- B. Wash down surfaces with a solution of mild detergent in warm water, applied with soft, clean wiping cloths, and take care to remove dirt from corners and to wipe surfaces clean.
- C. Upon completion of installation, thoroughly clean aluminum surfaces in accordance with AAMA 609 & 610.

3.06 PROTECTION

- A. Protect installed products from damage until Date of Preliminary Acceptance.

END OF SECTION 08 43 13

SECTION 08 16 13

FIBERGLASS DOORS

PART 1 - GENERAL

1.01 SECTION INCLUDES

- A. Fiberglass/aluminum hybrid doors. (FRP)
- B. Accessories as required for a complete installation.

1.02 REFERENCE STANDARDS

- A. AAMA 1304 - Voluntary Specification for Forced Entry Resistance of Side-Hinged Door Systems; 2002.
- B. AAMA 1503 - Voluntary Test Method for Thermal Transmittance and Condensation Resistance of Windows, Doors and Glazed Wall Sections; 2009.
- C. ASTM D1308 - Standard Test Method for Effect of Household Chemicals on Clear and Pigmented Organic Finishes; 2002 (Reapproved 2013).
- D. ASTM D256 - Standard Test Methods for Determining the Izod Pendulum Impact Resistance of Plastics; 2010, with Editorial Revision (2015).
- E. ASTM D543 - Standard Practices for Evaluating the Resistance of Plastics to Chemical Reagents; 2014.
- F. ASTM D570 - Standard Test Method for Water Absorption of Plastics; 1998 (Reapproved 2010).
- G. ASTM D635 - Standard Test Method for Rate of Burning and/or Extent and Time of Burning of Plastics in a Horizontal Position; 2014.
- H. ASTM D638 - Standard Test Method for Tensile Properties of Plastics; 2014.
- I. ASTM D790 - Standard Test Methods for Flexural Properties of Unreinforced and Reinforced Plastics and Electrical Insulating Materials; 2016.
- J. ASTM D2583 - Standard Test Method for Indentation Hardness of Rigid Plastics by Means of Barcol Impressor; 2013a.
- K. ASTM E84 - Standard Test Method for Surface Burning Characteristics of Building Materials; 2017.
- L. ASTM E283 - Standard Test Method for Determining the Rate of Air Leakage Through Exterior Windows, Curtain Walls, and Doors Under Specified Pressure Differences Across the Specimen; 2004 (Reapproved 2012).
- M. ASTM E330/E330M - Standard Test Method for Structural Performance of Exterior Windows, Doors, Skylights and Curtain Walls by Uniform Static Air Pressure Difference; 2014.
- N. ASTM E331 - Standard Test Method for Water Penetration of Exterior Windows, Skylights, Doors, and Curtain Walls by Uniform Static Air Pressure Difference; 2000 (Reapproved 2016).

- O. ASTM E2112 - Standard Practice for Installation of Exterior Windows, Doors and Skylights; 2007 (Reapproved 2016).
- P. NAAMM HMMA 861 - Guide Specifications for Commercial Hollow Metal Doors and Frames; 2014.
- Q. SDI 117 - Manufacturing Tolerances for Standard Steel Doors and Frames; 2013.

1.03 ADMINISTRATIVE REQUIREMENTS

- A. Coordination: Obtain hardware templates from hardware manufacturer prior to starting fabrication.
 - 1. Include coordination for automatic door control and remote door monitoring/access control system.

1.04 SUBMITTALS

- A. See Section 01 30 00 - Administrative Requirements, for submittal procedures.
- B. Product Data: Provide manufacturer's standard details, installation instructions, hardware and anchoring recommendations.
- C. Shop Drawings: Indicate layout and profiles; include assembly methods.
 - 1. Indicate product components, including hardware reinforcement locations and preparations, accessories, finish colors, patterns, and textures.
 - 2. Indicate wall conditions, door and frame elevations, sections, materials, gages, finishes, location of door hardware by dimension, and details of openings; use same reference numbers indicated on drawings to identify details and openings.
- D. Selection Samples: Submit two complete sets of color chips, illustrating manufacturer's complete line of finishes, colors, and textures.
- E. Verification Samples: Submit door surface samples for each finish specified, 10 inch by 10 inch in size, illustrating finishes, colors, and textures.
- F. Door Corner Sample: Submit corner cross sections, 10 inch by 10 inch in size, illustrating construction, finish, color, and texture.
- G. Test Reports: Submit certified test reports from qualified independent testing agency indicating doors comply with specified performance requirements.
- H. Manufacturer's Qualification Statement.

1.05 QUALITY ASSURANCE

- A. Manufacturer Qualifications: Company specializing in manufacturing products of the type specified in this section, with not less than ten years of documented experience.

1.06 COORDINATION

- A. Coordinate hardware template with framing.
- B. Coordinate with requirements for electrically operated doors and hardware.

1.07 DELIVERY, STORAGE, AND HANDLING

- A. Deliver materials in manufacturer's original, unopened, undamaged containers with identification labels intact.
- B. Deliver pre-assembled doors and frames with braces, spreaders, and packaging as required to prevent damage.
- C. Store materials in original packaging, under cover, protected from exposure to harmful weather conditions and from direct contact with water.
 - 1. Store at temperature and humidity conditions recommended by manufacturer.
 - 2. Do not use non-vented plastic or canvas shelters.
 - 3. Immediately remove wet wrappers.
- D. Store in position recommended by manufacturer, elevated minimum 4 inch above grade, with minimum 1/4 inch space between doors.

1.08 FIELD CONDITIONS

- A. Do not install doors until structure is enclosed.
- B. Maintain temperature and humidity at manufacturer's recommended levels during and after installation of doors.

PART 2 - PRODUCTS

2.01 MANUFACTURERS

- A. Fiberglass/Aluminum Composite Doors:
 - 1. Special-Lite, Inc; SL-17 with SpecLite 3 face sheets.

2.02 DOOR ASSEMBLIES

- A. Door Assemblies: Factory-fabricated, prepared and machined for hardware.
 - 1. Screw-Holding Capacity: Tested to 890 lbs, minimum.
 - 2. Surface Burning Characteristics: Flame spread index (FSI) of 0 to 25, Class A, and smoke developed index (SDI) of 450 or less, when tested in accordance with ASTM E84.
 - 3. Flammability: Self-extinguishing when tested in accordance with ASTM D635.
 - 4. Sizes: As indicated on drawings.
 - 5. Clearance between Door and Frame: 1/8 inch, maximum.
 - 6. Clearance between Bottom of Door and Finished Floor: 3/4 inch, maximum; not less than 1/4 inch clearance to threshold.

2.03 COMPONENTS

- A. Doors: Fiberglass construction with reinforced core.
 - 1. Thickness: 1-3/4 inch, nominal.
 - 2. Core Material: Urethane foam.
 - 3. Face Sheet Texture: Smooth.
 - 4. Subframe and Reinforcements: Provide manufacturer's standard aluminum subframe with 3/8" diameter full-width tie rods through extruded splines top and bottom as standard shaped stiles and rails reinforced to accept hardware as specified.
 - 5. Waterproof Integrity: Provide factory fabricated edges, cut-outs, and hardware preparations of fiberglass reinforced plastic (FRP); provide cut-outs with joints sealed independently of glazing, louver inserts, or trim.

6. Hardware Preparations: Factory reinforce, machine, and prepare for door hardware including field installed items; provide solid blocking for each item; field cutting, drilling or tapping is not permitted; obtain manufacturer's hardware templates for preparation as necessary.
- 7.

B. Hollow Metal Frames: Refer to Section 08 11 13 - Hollow Metal Doors and Frames.

C. Transom and Opaque Side Panels: Same construction as doors.

2.04 PERFORMANCE REQUIREMENTS

A. Provide door assemblies that have been designed and fabricated in compliance with specified performance requirements.

B. Forced Entry Resistance: Pass in accordance with AAMA 1304 test method, 300 pound load applied.

C. Water Leakage: No uncontrolled leakage on interior face when tested in accordance with ASTM E331 at differential pressure of 7.5 psf.

D. Air Leakage: Maximum of 0.1 cu ft/min/sq ft at 6.27 psf differential pressure, when tested in accordance with ASTM E283.

E. Structural Performance: Withstand positive and negative wind loads equal to 1.5 times design wind loads specified by local code without damage or permanent set, when tested in accordance with ASTM E330/E330M, using 10 second duration of maximum load.

F. Thermal Transmittance, Exterior Doors: AAMA 1503, U-value of 0.29, maximum, measured on exterior door in size required for this project.

G. Condensation Resistance, Exterior Doors: AAMA 1503, CRF of not less than 45.

H. Fiberglass Reinforced Plastic (FRP) Face Sheet Properties:

1. Izod Impact Resistance: ASTM D256, 15 ft lbf/inch of width, minimum, with notched izod.
2. Tensile Strength at Break: ASTM D638, 13,250 psi, minimum.
3. Water Absorption: ASTM D570, 0.16 percent, maximum, after 24 hours at 74 degrees F.
4. Flexural Strength: ASTM D790, 27,000 psi, minimum.
5. Barcol Hardness: ASTM D2583, minimum of 40 units.

I. Stain Resistance, ASTM D1308: Face sheet unaffected after exposure to red cabbage, tea, and tomato acid. Stain removed easily with mild abrasive or FRP cleaner when exposed to crayon and crankcase oil.

J. Chemical Resistance, ASTM D543. Excellent rating.

1. Acetic acid, Concentrated.
2. Ammonium Hydroxide, Concentrated.
3. Citric Acid, 10%.
4. Formaldehyde.
5. Hydrochloric Acid, 10%
6. Sodium hypochlorite, 4 to 6 percent solution.

2.05 FRP FINISHES

A. Abuse resistant engineered surface with protective coating and through-molded color.

1. Panel Texture: Pebble grain.
2. Color: As selected by Architect of Record from manufacturer's full line of colors.

2.06 ACCESSORIES

- A. Stops for Glazing: Fiberglass, unless otherwise indicated or required by fire rating; provided by door manufacturer to fit factory made openings, with color and texture to match door; fasteners shall maintain waterproof integrity.
 1. Exterior Doors: Provide non-removable stops on exterior side with continuous compression gasket weatherseal.
 2. Glazed Openings: Provide removable stops on interior side.
 3. Opening Sizes and Shapes: As indicated on drawings.
- B. Glazing: As specified in Section 08 80 00.
- C. Door Hardware: As specified in Section 08 71 00.

PART 3 - EXECUTION

3.01 EXAMINATION

- A. Verify actual dimensions of openings by field measurements before door fabrication; show recorded measurements on shop drawings.
- B. Do not begin installation until substrates have been properly prepared.
- C. Verify all require electrical and fire alarm work is completed and ready for installation of door frames.
- D. If substrate preparation is the responsibility of another installer, notify Architect/Engineer of Record of unsatisfactory preparation before proceeding.
- E. Proceed only after unsatisfactory conditions have been corrected. Commencement of work in this section will be an indication of the acceptance of substrate conditions and the Contractor will be held responsible for the satisfactory execution and results of the finished work.

3.02 PREPARATION

- A. Remove existing doors and frames, and dispose of all removed materials in accordance with local authorities having jurisdiction.
- B. Prepare surfaces using the methods recommended by the fiberglass door manufacturer for achieving the best result for the substrate under the project conditions.
- C. Clean and prepare substrate in accordance with manufacturer's directions.
- D. Protect adjacent work and finish surfaces from damage during installation.

3.03 INSTALLATION

- A. Install in accordance with manufacturer's instructions; do not penetrate frames with anchors.
- B. Install exterior doors in accordance with ASTM E2112.

- C. Install door hardware as specified in Section 08 71 00. Coordinate with electrically operated hardware as required.
- D. Set units plumb, level, and true-to-line, without warping or racking doors, and with specified clearances; anchor in place.
- E. Set thresholds in continuous bed of sealant.
- F. Separate surfaces from sources of corrosion or electrolytic action at points of contact with other materials with bituminous coatings or another means approved by Architect/Engineer of Record.
- G. Repair or replace damaged installed products.

3.04 TOLERANCES

- A. Clearances Between Door and Frame: Comply with related requirements of specified frame standards or custom guidelines indicated in accordance with SDI 117 or NAAMM HMMA 861
- B. Maximum Diagonal Distortion: 1/16 in measured with straight edge, corner to corner.

3.05 ADJUSTING

- A. Lubricate, test, and adjust doors to operate easily, free from warp, twist or distortion, and to fit watertight for entire perimeter.
- B. Adjust hardware for smooth and quiet operation.
- C. Adjust doors to fit snugly and close without sticking or binding.
- D. Adjust closers for full closure within force parameter requirements of ADA/IAC and MOPD

3.06 CLEANING

- A. Clean installed products in accordance with manufacturer's instructions prior to Board's acceptance.

3.07 PROTECTION

- A. Protect installed products from damage until Date of Substantial Completion.

END OF SECTION 08 16 13